

Aircraft Replacement Components and Pressure Gauges



8860A
Hose & Chuck Assembly
Fits 8885 Gauge
Length 18 Inches



8860R
Hose & Chuck Assembly
Fits 8844 Gauge
Length 18 Inches



8874-9
Copper Washer
Fits: 8874, 8875, 8876,
8921, 9043, 9044



8874-10
Washer
Fits: 8921,
8927, 9043



8874-12
Gauge Adapter
Fits: 8874, 8875
& 8876



8874-25
Bleeder Valve
Fits: 8874, 8875
& 8876



8874-22 Hose Assembly
Fits: 8874, 8875 and 8876



8921
Lock Chuck (Standard Bore)
T-Handle with .307-32
thread and 1/8 NPT
side hose connector.
Maximum operating
pressure of 3000 PSI



8927
Lock Chuck (Large Bore)
T-Handle with .485-26
thread and .375-24
side hose connector.
Maximum operating
pressure of 3000 PSI



9043
Lock Chuck (Standard Bore)
T-Handle with .307-32
thread and .375-24
side hose connector.
Maximum operating
pressure of 3000 PSI



9044
Lock Chuck (Standard Bore)
.307-32 thread and .375-24
side hose connector.
Maximum operating
pressure of 3000 PSI

Dial Gauges



8844-1
0-400 PSI & 0-2800 kPa
1/8 NPT Male
Thread For Mating
Replacement For:
8844 & 8844B



8874-28
0-400 PSI
1/4 NPT Male
Thread For Mating
Replacement For:
8874



8875-28
0-1500 PSI
1/8 NPT Male
Thread For Mating
Replacement For:
8875



8876-28
0-3000 PSI
1/4 NPT Female
Thread For Mating
Replacement For:
8876



8885L-1
0-200 PSI & 0-1400 kPa
1/8 NPT Female
Thread For Mating
Replacement For:
8885 & 8885-L



02500-DN-637
Used on the 8874, 8875
& 8876